






LIME WA INC
Accredited Lime Suppliers


Code of Practice
Product Information Sheet

Approved Laboratories



ChemCentre
EXPERT SOLUTIONS





PO Box 1230
BUNBURY
WA 6231

TEL: 1800 889 493 FAX: 9725 7724
MOB: Rick Gilmore 0428 615 161

GENERAL INFORMATION			
Pit Name	Lake Preston Lime	Date of Analysis	February 1st 2010
Location	Myalup	Laboratory No.	A06457/07A652-032
Product Description	Limestone	Product Screened	Yes
Weigh System ***	100 T Weighbridge	Screen Size (mm)	2.0 mm

*** This supplier uses an accredited weigh system verified by the Department of Consumer Protection

CODE OF PRACTICE APPROVED LABORATORY TEST REPORT				
	COMPOSITE SAMPLE	RANGE FOR PIT	COMPOSITE SAMPLE	RANGE FOR PIT
Sieve Range (mm)	% Weight		% Neutralising Value	
0.000 – 0.125	8.0	8.0 - 14.8	86.0	80.7 - 89.6
0.125 – 0.250	32.3	22.2 - 38.6	73.4	68.2 - 81.3
0.250 – 0.500	31.2	25.5 - 31.2	75.6	74.0 - 76.9
0.500 – 1.000	16.1	12.4 - 20.9	70.6	67.0 - 72.0
> 1.000	12.4	6.7 - 19.9	87.7	81.7 - 90.2
Weighted Average NV			76.5	72.7 - 79.9
Bulk NV	76.6	73.2 - 79.1		
Calcium (Ca) (1 M HCl)	28.6	28.6 - 30.5		
Magnesium (Mg) (1 M HCl)	1.1	0.8 - 1.4		
Sodium (Na) (1 M HCl)	0.2	0.1 - 0.2		
Moisture Content	7.2	0.2 - 7.2		

Statement by Supplier : The above composite analysis has been determined from an audit sample and a pit sample tested by Code of Practice approved laboratories, and is a true representation of the product being supplied from the nominated pit. Pit ranges have been calculated from the last 3 samples analysed.

Date:- Position:- Signature:-

Disclaimer : Lime WA Inc. requires members to provide the above details in accordance with the industry Code of Practice requirements but makes no claims and provides no guarantees on the quality or suitability of the product supplied. Lime WA Inc. is not responsible for any claims and/or liabilities arising from the supply and/or use of the product supplied. However, users are invited to contact the association on 0419 575 737 in the event of any dissatisfaction with the product description provided by accredited lime suppliers.